



- High quality mechanical seal assures long life.
- Stainless steel pump body and cast iron base for heavy duty.
- Excellent motor protection thanks to winding thermostat.
- Wear resistant shaft and impeller.

Model: **MAXIVORT 50 36/14**
 Part number: **N2091230**
 Barcode: **7630046619169**

Submersible pump for waste water and drainage applications.
 MAXIVORT 50-36/14 has been especially designed for very demanding heavy duty applications. The 50 mm free passage allows reliable handling of solids without risk of blocking.



APPLICATIONS

Drainage of cesspools, flood water removal and sewage transfer from sump.

ABSORBED POWER	2.200 W	MAX.DEPTH OF IMMERSION	7 m
VOLTAGE	230 V	MAX.TEMPERATURE OF FLUID	35°C
FLOW RATE	36.000 l/h	MAX.SIZE OF IMPURITIES	50 mm
MAX. HEAD	14 m	START / STOP	614mm/238mm
RATED CURRENT	7.2 A	WEIGHT	18.5 kg
PUMP BODY	Stainless Steel	PACKAGING DIMENSIONS	23 x 19.5 x 44 cm
DELIVERY PORT	59,61 mm (2" M)	PCS PER PALLET	36
MINIMUM DRAINING LEVEL	66 mm		